

DS-KLM28-12

Smart cabinet - main module (8 inch touch screen)



- Integrates face verification, liquid crystal display, touch interaction, card reading, voice, lock control, electromagnetic lock, etc.;
- Based on the Internet of Things technology, AI technology, computer communication technology;
- Max Qty of sub-cabinets: 16
- Operating system: Android OS
- Screen: 8-inch IPS touch screen, resolution 800*1200
- Authentication: Face, M1 card, password;
- Open method: authentication, remote control, mechanical key and one-click full opening (only for administrator) to open the cabinet;
- Capacity: 20,000 faces, 200,000 cards, 100,000 events
- Communication: LAN, WIFI
- Dimension: 970mm*477mm*1,880mm (Width*Depth*Height)
- Working mode: Guest mode, Private mode and Hybrid Mode (Guest+ Private)
- Cabinet allocation: one person to one grid, one person to multiple grids and multiple people to one grid. The allocation supports all cabinet grid allocation, free cabinet grid allocation, and designated cabinet grid allocation.
- Advertisement: supports carousel standby screen pictures (up to 5 pictures).
- Plan template: supports to configure device usage plan templates, set open and disabled time periods for access operations, contains one weekly plan template and seven holiday plan templates.
- Time calibration function: built-in RTC, supports NTP time calibration, manual time calibration and automatic time calibration. Data storage: When the power is off, the cabinet keeps its original state and saves the data automatically; the cabinet will work normally even offline, and events resumes transmission after the network is connected.
- Camera: 2M pixels, wide dynamic range and low light binocular camera;
- Audio: audio input and output, built-in omnidirectional microphone and speaker;

Parameters

Screen	
Size	8 inch
Operation method	IPS touch screen
Interface	
Network interface	1 RJ45, 10/100/1000 M self-adaptive
RS-485	1
General	
Power supply	100~230 VAC
Working temperature	-10°C~50°C
Net Weight	50kg
Protective level	Indoor

Available Model

DS-KLM28-12

Dimension

